



QUV (and QCT) Space Saver Frames

QUV® space saver frames from Q-Lab help preserve space in crowded labs with multiple QUV test chambers. By allowing two QUV testers to be stacked, floor space efficiency is maximized.

Features and Benefits

- Saves valuable floorspace in crowded labs
- Anodized aluminum construction resists corrosion
- Compact design to allow for easy access to both units
- Leveling feet for uneven surfaces
- Two models for compatibility with all new and existing QUV testers




Stacking testers on the space saver frame allows easy access to both machines.

Description

Space saver frames are designed in two models for compatibility with virtually any combination of new and existing QUV testers. QCT testers on space saver frames require factory installation. Heavy-duty, anodized aluminum construction helps the space saver frame resist corrosion and keep its appearance identical to the QUV units. Leveling feet permit secure installation on uneven floor surfaces.

Model Types, Dimensions, and Shipping Weight

QUV space saver frames are available in two different models (Note: see instructions on next page to find the correct model).



Model	Compact	Standard
Compatible with QUV testers	New & series 81+	Series 1-80
Plumbing	Fully integrated	External ¹
Compatible with QCT testers	No	Yes ²
Dimensions (h x w x d)	184 x 127 x 62 cm (72.5 x 50 x 24.5 in)	202 x 127 x 62 cm (79.5 x 50 x 24.5 in)
Required Water Input/Drains	One Water Input One Drain	Two Water Inputs Two Drains
Weight	34 kg (75 lb.)	34 kg (75 lb.)

1. Spray models require additional external plumbing boxes.

2. New, factory-installed QCT testers only. Requires top and bottom cycle timer boxes.

Instructions For Identifying The Correct Space Saver Frame Part Number

1. Select the appropriate space saver frame letter designation (A, B, C, D, E) from the Space Saver Frame Compatibility Matrix below by identifying the desired bottom and top configuration of your QUV (or QCT) testers.
2. Using the letter from Step 1, select the appropriate part number(s) in the Part Number Identification Table.

Space Saver Frame Compatibility Matrix

Bottom Unit	Top Unit	New QUV/basic, QUV/se	New QUV/spray ¹	New QUV/spray w/ standalone REPUR ¹	Retrofit Series 81+ QUV/basic, QUV/se	Retrofit Series 81+ QUV/spray ¹	Retrofit Series 81+ QUV/spray/REPUR ^{1,2}	Retrofit Series 1-80 QUV/basic, QUV/se	Retrofit Series 1-80 QUV/spray ¹	Retrofit Series 1-80 QUV/spray/REPUR ^{1,2}	New QCT
New QUV/basic, QUV/se		A	–	–	A	–	–	D	–	–	–
New QUV/spray		B	B	–	B	B	–	D	D	–	–
New QUV/spray w/standalone REPUR		A	–	A	A	–	A	D	–	D	–
Retrofit Series 81+ QUV/basic, QUV/se		–	–	–	C	–	–	D	–	–	–
Retrofit Series 81+ QUV/spray		C ³	–	–	C	C	–	D	D	–	–
Retrofit Series 81+ QUV/spray/REPUR ²		C ³	–	–	C	–	C	D	–	D	–
Retrofit Series 1-80 QUV/basic, QUV/se		D	–	–	D	–	–	D	–	–	–
Retrofit Series 1-80 QUV/spray		D ³	D	–	D	D	–	D	D	–	–
Retrofit Series 1-80 QUV/spray/REPUR ²		D ³	–	–	D	–	D	D	–	D	–
New QCT		–	–	–	–	–	–	–	–	–	E

1. If there is only one QUV/spray unit, it should always be the bottom unit on the space saver frame.
2. Requires purchase of a standalone repurification system. Integrated repurification system cannot be reused.
3. For field retrofits of QUV/spray units with a new non-spray unit, space saver frame is shipped disassembled. Consult factory.

Part Number Identification Table

	A	B	C	D		E	
Model	Compact			Standard			
Space Saver Frame	V-60227-K	V-60228-K	V-60229-K	V-440-K			
Bottom Plumbing Box ¹	–	–	–	120V V-2428-K	230V V-2440-K	–	–
Top Plumbing Box ¹	–	–	–	V-2429-K	V-2441-K	–	–
Bottom Cycle Timer Box ²	–	–	–	–	–	120V C-4146-K-INST	230V C-4147-K-INST
Top Cycle Timer Box ²	–	–	–	–	–	–	–

1. Plumbing boxes or standalone repurification systems are required for each QUV/spray tester used in configuration D.
2. Cycle timer boxes are required for each QCT tester used in configuration E.

Warranty

The space saver frame is guaranteed against defects in workmanship or materials for one year. Liability is limited to replacing or repairing any part or parts which are defective in materials or workmanship and are returned to our factory, shipping costs prepaid. Liability in all events is limited to the purchase price paid. Damage due to accident or abuse is not covered. Labor and travel costs are not covered. Q-Lab Corporation makes no other warranties, including implied warranties of merchantability or fitness for a particular purpose, except as may be expressly provided by Q-Lab Corporation in writing. Q-Lab Corporation shall not be liable for any incidental, consequential, special, or contingent damages arising out of the sale or use of any product.

Q-Lab Corporation

www.q-lab.com



Q-Lab Headquarters
Westlake, OH USA
Tel: +1-440-835-8700
info@q-lab.com

Q-Lab Florida
Homestead, FL USA
Tel: +1-305-245-5600
q-lab@q-lab.com

Q-Lab Europe, Ltd.
Bolton, England
Tel: +44-1204-861616
info.eu@q-lab.com

Q-Lab Arizona
Buckeye, AZ USA
Tel: +1-623-386-5140
q-lab@q-lab.com

Q-Lab Deutschland GmbH
Saarbrücken, Germany
Tel: +49-681-857470
vertrieb@q-lab.com

Q-Lab China 中国代表处
Shanghai, China 中国上海
电话: +86-21-5879-7970
info.cn@q-lab.com