

Technical Manual

Q-FOG

Cyclic Corrosion Tester



Applicable for Serial Numbers: XX-XXXX-38 thru -40



Q-Lab Corporation

**Q-Lab Headquarters
United States**
Tel. +1 440-835-8700
info@q-lab.com

**Q-Lab Europe, Ltd.
England**
Tel: +44 (0) 1204 861616
info.eu@q-lab.com

**Q-Lab Deutschland GmbH
Deutschland**
Tel: +49 681-85747-0
vertrieb@q-lab.com

**Q-Lab 中国代表处
中国上海**
电话: +86 21-5879-7970
info.cn@q-lab.com

www.q-lab.com

The most trusted name in weathering

7. Sample Mounting (Revised February 2009)

Test Specimens can be mounted in panel racks or suspended from hanging rods. Typically, flat panels are mounted in racks and 3D parts are suspended from hanging rods.

RACKS	length	maximum weight per rack	number of panels per rack	number of racks per chamber
model 600	27.5" (70cm)	250 pounds	17 (1.5" apart)	8
model 1100	33.5" (85cm)	250 pounds	21 (1.5" apart)	10

RODS	length	maximum weight per rod		number of rods per chamber
model 600	29.5" (75cm)	100 pounds		6
model 1100	36" (91cm)	100 pounds		8



Panel Racks (some panels removed to show rack)



Hanging Rods